



Hexoto Industries Pvt. Ltd. takes pleasure in introducing itself as a company, which is wholly involved in manufacturing and wholesale distribution of Rotary Joints, Rotary Unions, Roto Seal, Mechanical Seals, Steam Hose Pipe, SS Corrugated Pipe and many more.





ROTO 101



Available size	: 1/4" to 2"
Housing	: Brass
Shaft	: S.S.
Seals	: S.S. Spring and Carbon Filled PTFE Teflon
RPM	: 1/4" to 3/4"=3500 rpm. 1" to 2"=1000 rpm Maximum
Flow	: Mono Flow/Dual Flow
Media	: Water, Oil, Gas, Chemical, Air

ROTO 102



Available size	: 1/4" to 2"
Housing	: Aluminium, C.I.
Shaft	: M.S.
Seals	: Carbon Teflon(CFT)
RPM	: 1/4" to 2"=2500 rpm.
Flow	: Mono Flow/Dual Flow
Media	: Water, Oil, Gas, Chemical, Air

ROTO 103



Available size	: 1/4" to 2"
Housing	: S.S. 304
Shaft	: S.S.
Seals	: Carbon Teflon(CFT)
RPM	: 1/4" to 2"=2500 rpm.
Flow	: Mono Flow/Dual Flow
Media	: Water, Oil, Gas, Chemical, Air

S SERIES



Available size	: 1/2" to 2 1/2"
Housing	: C.I.
Shaft	: M.S., S.S.
Seals	: Carbon Graphite, Carbon Teflon(CFT)
Flow	: Mono Flow/Dual Flow
Media	: Water, Oil, Gas, Chemical, Steam

C SERIES



Available size	: 1/2" to 2 1/2"
Housing	: C.I.
Shaft	: M.S., S.S.
Seals	: Carbon Graphite, Carbon Teflon(CFT)
Media	: Water, Oil, Chemical, Steam

H SERIES



Available size	: 1/2" to 2 1/2"
Housing	: C.I.
Shaft	: M.S., S.S.
Seals	: Carbon Graphite, Carbon Teflon(CFT)
Flow	: Mono Flow/Dual Flow
Media	: Water, Oil, Gas, Chemical, Steam



D SERIES



MECHANICAL SEAL



HHSEAL



Available size : 1/2" to 2 1/2"
Housing : C.I.
Shaft : M.S., S.S.
Seals : Carbon Graphite,
 Carbon Teflon(CFT)
Media : Water, Oil, Chemical, Steam

Seal Characteristics • Single acting
 • Unbalanced
 • Inside mounted
 • Single helical coil spring
 • Independent of direction of rotation
Operating Limit
 • Temperature : -20° to 200°C
 • Pressure : 14 Bar(Max.)
 • Velocity : 20 m/sec

Seal Characteristics • Single acting
 • Unbalanced
 • Inside mounted
 • Single helical coil spring
 • Independent of direction of rotation
Operating Limit
 • Temperature : -20° to 180°C
 • Pressure : 12 Bar(Max.)
 • Velocity : 20 m/sec

SS CORRUGATED PIPE



HOSE PIPE



CARBON TEFLON SEAL



Size : 1/4" To 4"
Available: S.s 304,s.s 316 As Per Requirement
Temp : 50c. To 350c
Clamp : Flange Connection,thread Connection,
 push Fitting
Media : Steam Hose,water, Fluid Oil,hot Oil,

Size : 1/4" To 4"
Available: Rubber Hose As Per Requirement
Temp : 50c. To 350c
Clamp : Flange Connection,thread Connection,
 push Fitting
Media : Steam Hose,water, Fluid Oil,hot Oil,

Teflon Ring set and mechanical seal which are currently and regularly being utilized in Power Projects.



PTFE SEAL



We offer wide range of P.T.F.E. (Teflon) that is manufactured in compliance with the high standard.

CARBON PRODUCT



We offer all types of Carbon Ring set and mechanical seal utilized in Power Projects, Chemical Industries.

FITTINGS



The company has a wide range of a variety of **fittings**. They offer to all of their clients based on their exact requirements. They offer fitting according to industry standards and thus you can remain to rest assured of getting all top-quality products

Corporate office:
A/806 The Gatway, Near Parikh Hospital,
S P Ring Road, Nikol 382 350

Factory Address:
C/45, Shreenath Estate, Nr. Ghanti Bus Stand, Bhilwada,
Amraiwadi, Ahmedabad - 380 026

Web: www.hhrotaryjoint.com
Email: info@hhrotaryjoint.com
Phone: +91-9998347003, +91-9879476160